

Caroma®

Liano


Vitreous China 4.5/3 litre Dual Flush
Wall Faced Close-Coupled Toilet Suite



CI/SfB	(74.1)	g3
Date	January 2014	

Supersedes all previous issues

3.76.1





A sharp and symmetrical design for a contemporary look and feel, the **Liano** wall faced close coupled toilet suite conceals plumbing fittings for an aesthetically pleasing finish. The pan connection system includes the patented Caroma Uni-Orbital® Connector for increased installation flexibility. The Caroma Uni-Orbital® Connector extends to any position in a 50mm radius, unlike traditional connectors that only move backwards and forwards. The setout range is from 60mm – 205mm with a recommended setout of 140mm. The suite is targeted to commercial projects, but is also suitable for domestic applications. Fitted with chrome plated push buttons, the smooth sided pan design with the great looking thin lid, soft close seat with quick release offers a seamless finish to your bathroom.

Pan: **Liano** 4.5 litre full flush washdown pan with a fully glazed rim and trap.

Traps: Universal trap for S or P-trap installations.

Cisterns: **Liano** Cistern – has a free fitting lid and is suitable for domestic and light commercial applications. Available as internal overflow. Standard back entry only. Cistern inlet stop valve and inlet flex tube connection is concealed within the cistern and is included.

Vandal Resistant Conversion Kit – A simple to install conversion kit is available for the standard mechanism to lock the lid onto the cistern, recommended for use in heavy duty commercial areas. Code No.750109.

Important: Working pressure minimum 30kPa to maximum 1000kPa flow pressure. Rain water tank compliant. Accurate wall setout for B.S.P. 1/2" Nipple water inlet connection is essential.

Fixing: The cistern is fixed directly to the pan with a robust concealed base fixing system without the need for wall fixing.

Seats: The **Liano** soft close quick release toilet seat is provided as standard with the Liano suite. A quality solid section compression moulded toilet seat, fitted with buffers and metal hinges.

Colours: White only.

Installation: The installation of the toilet suite shall be in accordance with the normal minimum drainline grade requirements in AS/NZS 3500.2.

Dimensions: All dimensions are in millimetres and are subject to normal manufacturing variations. Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications without notice.

